



Industrial



Test




Comm



Broadcast

100W, 9 to 53V Input Non-isolated DC-DC Converters



Features	Benefits
• 100W 4.5 or 8A Output	
• 1/32nd brick Footprint	
• Wide Output Adjustment 3.3 to 16.5V or 5 to 30V	
• Minimal External Components Needed	

Specification			
Model			
		i3AW008A033V	
		i3A4W005A150V	
DC Output Voltage (1)	V	3.3 - 16.5	5 - 30
DC Input Voltage	V	9 - 53 (Turn on at 10V or greater)	
Efficiency (Typical)	%	89 - 96.5	95.5 - 98
Output Voltage Tolerance	%	±4	
Switching Frequency	kHz	450	400
Line Regulation	%	0.3%	0.2%
Load Regulation	%	0.7%	0.5%
External Load Capacitance	uF	0 - 1200	
Output Ripple and Noise	mVpp	20	40
Overcurrent Protection (Typ)	A	14	9
Remote On / Off	-	Negative Logic (For Positive Logic Contact Factory)	
Remote Sense	-	(+) Sense, compensating up to 5% of output voltage	
Power Good	-	Optional, contact factory for status	
Operating Temperature	°C	-40°C to 125°C (see thermal data on website)	
Storage Temperature	°C	-55°C to 125°C	
Safety Agency Certifications	-	UL/EN60950, CE Mark	
Weight	g	8	
Size (LxWxH)	mm	19.1 x 23.4 x 9.6	
Warranty	yrs	3	


Note: (1) Output voltage cannot exceed input voltage (see graph on page 2)

Model Selector


Model	Input Voltage (V)	Output Current (A)	Output Voltage (V) ⁽¹⁾	Positive Logic On/Off	Negative Logic On/Off
i3A4W008A033V-001-R	9 - 53	8	3.3 - 16.5	-	Yes
i3A4W005A150V-001-R	9 - 53	4.5	5 - 30	-	Yes

Note: (1) Output voltage cannot exceed input voltage (see graph below)


Outline Drawing i3AW



Output Voltage vs Input Voltage Operating Range



Output Voltage vs Input Voltage Operating Range



Pin Assignment

PIN	Function	PIN	Function
1	VIN (+)	5	PWR GOOD (Option)
2	ON / OFF	6	TRIM
3	VIN (-)	7	SENSE (+)
4	VOUT (-)	8	VOUT (+)



TDK-Lambda France SAS

3 Avenue du Canada
Parc Technopolis
Bâtiment Sigma
91940 les Ulis
France
Tel: +33 1 60 12 71 65
Fax: +33 1 60 12 71 66
france@fr.tdk-lambda.com
www.fr.tdk-lambda.com



Italy Sales Office

Via dei Lavoratori 128/130
20092 Cinisello Balsamo (MI)
Italy
Tel: +39 02 61 29 38 63
Fax: +39 02 61 29 09 00
info.italia@it.tdk-lambda.com
www.it.tdk-lambda.com



Netherlands

info@nl.tdk-lambda.com
www.nl.tdk-lambda.com



TDK-Lambda Germany GmbH

Karl-Bold-Strasse 40
77855 Achern
Germany
Tel: +49 7841 666 0
Fax: +49 7841 5000
info.germany@de.tdk-lambda.com
www.de.tdk-lambda.com



Austria Sales Office

Aredstrasse 22
2544 Leobersdorf
Austria
Tel: +43 2256 655 84
Fax: +43 2256 645 12
info@at.tdk-lambda.com
www.de.tdk-lambda.com



Switzerland Sales Office

Bahnhofstrasse 50
8305 Dietlikon
Switzerland
Tel: +41 44 850 53 53
Fax: +41 44 850 53 50
info@ch.tdk-lambda.com
www.de.tdk-lambda.com



Nordic Sales Office

Haderslevvej 36B
DK-6000 Kolding
Denmark
Tel: +45 2911 9556
info@dk.tdk-lambda.com



TDK-Lambda UK Ltd.

Kingsley Avenue
Ilfracombe
Devon EX34 8ES
United Kingdom
Tel: +44 (0) 12 71 85 66 66
Fax: +44 (0) 12 71 86 48 94
powersolutions@uk.tdk-lambda.com
www.uk.tdk-lambda.com



TDK-Lambda Ltd.

Kibbutz
Givat Hashlosha 48800
Israel
Tel: +9 723 902 4333
Fax: +9 723 902 4777
info@tdk-lambda.co.il
www.tdk-lambda.co.il



C.I.S.

Commercial Support:
Tel: +7 (495) 665 2627
Technical Support:
Tel: +7 (812) 658 0463
info@tdk-lambda.ru
www.tdk-lambda.ru

Local Distribution

